

G80 Webbing Sling Connector (TCSH001)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)						N.W. (kg/pc)
			A	B	K	W	G	E	
6-8	1.12	4.48	15	60	56	40	18	7	0.2
7/8-8	2.0	8.0	20	61.5	63.7	40	24	9.5	0.3
10-8	3.15	12.6	24	66	83	39	30.5	11	0.68
13-8	5.3	21.2	28	88	93.7	55	36.8	16.5	1.47
16-8	8	32	34.5	108	120	65.5	45.2	19.8	2.3
20-8	12.5	50	41	129	138	80	51.8	23	3.3





G80 Omega Link (TCSH002)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			A	B	Φ	H	L	
6-8	1.12	4.48	8	41	20.5	25	52	0.13
7/8-8	2.0	8.0	10	52	23.5	35	68.5	0.21
10-8	3.15	12.6	12	62	31.5	40.5	81	0.36
13-8	5.3	21.2	15	81	41	54	108	0.71
16-8	8	32	19	99	49.5	64	126	1.30
20-8	12.5	50	23	118	58	75.6	152	2.2





G80 Clevis Link (TCSH003)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)						N.W. (kg/pc)
			A	B	D	H	K	L	
7/8-8	2	8.0	9.5	33	27	45	69	102	0.22
10-8	3.15	12.6	13	45.5	27	45	72	116	0.45





G80 Clevis Choke Link(TCSH004)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)						N.W. (kg/pc)
			A	B	D	H	K	L	
10-8	3.15	12.6	12.5	46	50	140	173	209	0.82
13-8	5.3	21.2	16.5	58	66	140	182	227	1.75





G80 Long Shape Omega Link (TCSH005)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			A	B	D	K	L	
6-8	1.12	4.48	8	28	20	47.5	75	0.12
7/8-8	2.0	8.0	10.5	32.5	25	59	92	0.17
10-8	3.15	12.6	13	45.5	30	78.5	123	0.43
13-8	5.3	21.2	15	57.5	46	94	154	1.00





G80 Sling Hook with Link (TCSH006)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			E	B	Φ	K	L	
7/8-8	2	8	32.5	18	37	87	149	0.52





G80 Clevis Swivel Self-Locking Hook (TCSH007)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			Φ	B	C	L	E	
6-8	1.12	4.48	34	8	32	180	28	0.73
7/8-8	2	8	46	9.5	37	227.5	34	1.3





G80 U.S. Eye Self-Locking Hook (TCSH008)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (lbs)	B.L (lbs)	Dimension (mm)						N.W. (kg/pc)
			Φ1	E	2	↕	K	L	
7/8-8	4500	18000	25	35	42	29.5	132	173.5	0.98
10-8	7100	28400	32.5	46	55	34.5	171	220.5	1.85
13-8	12000	48000	42	56	64	41.5	312	273.5	3.75