
G80 U.S. Type Clevis Slip Hook with Latch (TCSH069)






- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (lbs)	B.L (lbs)	Dimension (mm)				N.W. (kg/pc)
			A	B	E	L	
1/4"	3500	14000	11.5	89	29	137.5	1.1
3/8"	7100	28400	14.5	117	38	179	2.65
1/2"	12000	48000	17.8	139	47	217.5	4.95
5/8"	18100	72400	20.8	161.5	52	253	8.15
3/4"	28300	113200	24.5	187	56	294	12.12

G80 High Tensile Hook (TCSH071)






- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)				N.W. (kg/pc)
			L	A	B	R	
9-8	2.5	10	143	13.5	90.5	18.5	0.5
11-8	3.75	15	177	15.5	109.5	22	0.85
13-8	5.4	21.6	205	17.7	129	25.5	1.38

G80 Sliding Choke Hook (TCSH072)






- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			Φ	A	B	E	L	
3/8-1/2	1.6	8	17	50	71	21	132	0.68
5/8	2	10	22	63.5	79	23	151.5	1.21
3/4	3	15	28	69	103	29	170	1.99
1	5	25	32.5	85.7	105	38	213	4.18

G80 Clevis Chain Clutch (TCSH073)






- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			A	B	C	E	L	
6-8	1.12	4.48	7.5	7.5	33	26	73.5	0.17
7/8-8	2	8.0	9.5	9.5	45	36	101	0.41
10-8	3.15	12.6	13	13	55	48	138	0.97
13-8	5.3	21.2	18	16	75	59	177	2.01
16-8	8	32	21	21	93	73	220	3.32
18/20-8	12.5	50	22	22	99	78	238	6.2
22-8	15	60	25.5	25.5	118	98	295	8.5

G80 European Type Connecting Link (TCSH074)






- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)				N.W. (kg/pc)
			A	L	K	H	
6-8	1.12	4.48	15	58	42	7.0	0.08
7-8	1.5	6	19	71.8	54.8	8.5	0.145
7/8-8	2	8	18	79.5	62.5	8.5	0.146
8-8	2	8	18	79.5	60.5	8.5	0.16
10-8	3.15	12.6	25	93	68	10.8	0.30
13-8	5.3	21.2	29	117	87	15	0.70
16-8	8	32	34.5	148	108.4	19.8	1.1
18-8	10	40	38	154	112	21	1.84
18/20-8	12.5	50	41	169.5	121.5	24	1.8
22-8	15	60	48	193.5	141.5	26	3.2
26-8	21.2	84.8	57.5	220	158	30	4.5
32-8	31.5	126	67	281	205	37	9

G80 U.S Type Connecting Link (TCSH075)






- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (lbs)	B.L (lbs)	Dimension (mm)				N.W. (kg/pc)
			A	L	K	H	
1/4"	3250	13000	19.5	69	55	7	0.24
5/16"	4500	18000	18	79.5	62.5	8.5	0.32
3/8"	6600	26400	27	91.5	68.5	11.5	0.58
1/2"	11250	45000	35	111	81	15	1.2
5/8"	16500	66000	42	137.5	95.5	21	2.42
3/4"	23000	92000	43	171	126	22.5	3.89
7/8"	28750	115000	48	190.5	141.5	24.5	6.08

G80 U.S Type Connecting Link (TCSH076)





- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (lbs)	B.L (lbs)	Dimension (mm)				N.W. (kg/pc)
			A	L	K	H	
1/4"	3500	14000	16.5	67	51	8	0.286
5/16"	4500	18000	17	78.5	58.5	10	0.32
3/8"	7100	28400	22	87.6	63.6	12	0.73
1/2"	12000	48000	28.5	115.5	85.5	15	1.67
5/8"	18100	72400	33	143	106	18.5	2.86
3/4"	28300	113200	41	162	116	23	5.00
7/8"	34200	136800	50.5	188.5	136.5	26	7.50
1"	47700	190800	57	214.5	152.5	31	11.03
1-1/4"	72300	289200	65	265	188.7	38	20.38